

Specially designed for **John Deere 5000 series** tractors

**GREENSYSTEM**...

## TECHNICAL SPECIFICATIONS


Specifications	Deluxe Hydraulic	Deluxe Mechanical
Model	MB3012H	MB3012M
Number of bottoms	2	
Reversing mechanism	Hydraulic	Mechanical
Size of plough (L x W x H)	1865 X 1130 X 1305 mm (73.42" X 44.49" X 51.38")	1800 X 1140 X 1380 mm (70.86" X 44.88" X 54.33")
Suitable tractor rating	Mini. 42-45 HP with SCV	Mini. 42-45 HP
Weight of machine	400 kg	390 kg
Hitch type	CAT II	
Working width per bottom	330 mm	
Working depth	204-330 mm	
Underframe clearance	595 mm	
Interbody clearance	610 mm	
Soil opener	Edge type	





Hydraulic cylinder

Safe and quick turnover action, bears high impact of load. Less effort required and less operator fatigue.



**Modular assembly** 

Reduces soil resistance with the strong & smooth mold board. Load reduction results in better fuel efficiency.




Frog assembly with bar point

Helps to replace worn out components easily. Also acts as support for all ground engaging tools.



Interbody & underframe clearance

Adequate interbody and underbody clearance helps to work in grassy land. Better soil inversion.



Heavy duty needle bearing

Increases reliability and durability of implement. Provides smooth working.

## John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in







