

Specially designed for **John Deere 3000 series** tractors



## **FLAIL MOWER**

Model	Unit	SM5130
Overall Length	mm	1300
Overall Width	mm	1068
Overall Height	mm	951
Working Width	mm/inch	1150/45
Suitable Tractor Rating	HP	20 to 40
Hitch Type		CAT I, 3 point linkage
Number of Hammer		14
PTO Input Speed	RPM	540
Rotor Speed	RPM	2083
Side Transmission		3 Belts, BX Type
Side Shift		Fix Mounting
Rotor Diameter	mm/inch	159/6.50
Rotor Swing Diameter	mm/inch	378/15
Weight	kg	325



## **SALIENT FEATURES**



**Durable Blade**Heavy duty blade ensures long life of blade.



**Side Discharge Section**4 different adjustments
for discharge section to
cover more effective area



Sturdy Main Frame Robust frame with stiffeners and Tool box mounted on frame



Long Lasting Rakes
Equidistant rakes provide
uniform aggregation
to chopper blades



Heavy Duty Gear Box Gear box desinged for heavy loads and act as shock absorber for back shocks



Discharge Unit Cover Can be used as green fodder chopper during non-season time

## John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in







