

Specially designed for **John Deere 5000 series** tractors

GREENSYSTEM...

TECHNICAL SPECIFICATIONS

Model	PH5012	PH5015	PH5017
Gear Box	Single Speed		
LxWxH(mm)	975 x 1365 x 1100	975 x 1610 x 1100	975 x 1855 x 1100
Working Width (mm/inch)	1250 / 49.2	1500 / 59.1	1750 /68.9
Working Depth (mm/inch)	100-200 / 4-8	100-200 / 4-8	100-200 / 4-8
Suitable Tractor Rating	50 HP (37.2 kW) & above	55 HP (41 kW) & above	60 HP (44.7 kW) & above
No. of Blades	10	12	14
Weight (kg)	390	430	470



SALIENT FEATURES



Blades
High quality corrosion
resistant boron steel blades
with 12 mm thickness
and 285 mm length



Blade Rotors
Each rotor has its own
gear & bearings
arrangement to enable
trouble free tilling



PTO Shaft
Drive shaft with safety
limiter & shear bolts protects
implement from damage



Leveling Bar
Leveling bar with scales for uniform
leveling of tilled surface. Lead screw
mechanism for easy adjustments.



Swinging Brackets
Brackets for 3-point
attachment with tractor

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in







