

Specially designed for **John Deere 5000 series** tractors



DESCRIPTION	SPECIFICATION
Model Number	TS3001
Number of Tines	1
Hitch Type	3 Point, CAT II
Overall Length	740 mm
Overall Width	960 mm
Overall Height	1400 mm
Weight	135 kg
Suitable Tractor Rating	50 HP & Above
Maximum Working Depth	Upto 558 mm
Thickness of the Tine	36 mm
Depth Adjustment	Upto 50 mm

SALIENT FEATURES



Specially designed shank

Combination of curved & straight shapes reduce load on the tractor.



Protective shear bolt

The shear bolt works as a mechanical fuse under overload conditions and protects shoe & shovel.



High quality steel alloy

The shoe & shovel are made of high quality carbon steel, which results in low wear and tear.



Dual hitch points

Specially designed hitch geometry provides two adjustable points for depth adjustment.







Heavy duty mainframe

The mainframe of this subsoiler is specially designed for heavy duty applications and high durability.

For more information, please contact our authorised dealer or nearest area office. Sales & Service through John Deere authorized dealers only.



3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra.

GREENSYSTEM

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.