

Specially designed for **John Deere 5000 series** tractors

GREENSYSTEM_{TM}

Parameter	Unit	RB0308	RB0310	RB0311
Dimension (LxWxH)	mm	1435x1450x1250	1550x1450x1250	1750x1250x1450
Working Width	mm	800	1060	1175
Overall Machine Weight	kg	520	630	610
Bale Size	mm	760x610	930x610	1050x500
	ft	2.5x2	3x2	3.44x1.64
Bale Weight (Approx.)	kg	25 to 35 18 to 24		
Binding Material		Jute Twine		
Bale Counter Type		Electronic Display		
Lubrication		Centralized Self Lubrication		
Bale Ejection		Electronic button with hydraulic operation		
Bale Density		Adjustable		
Support Wheel		Agricultural Rib Tire		
No. of Rollers		12 10		10
Hitch Type		3 Point Hitch, Cat II		
Suitable Tractor				
- Rating	HP	35 and	above	45 and above
- PTO	RPM	540		
- Clutch Type		Dual		



COMPACT ROUND BALER



Bale Density Lever Adjusts different bale density based on the requirement.



Twine Setting Disc Provides 10, 12 & 14 number of rotations twine binding setting.



Bale CounterCounts the number of bales produced automatically.



Compact Bale SizeEasy to handle & store.
Edge to edge binding.



Low Roller Space Provides better straw picking & gathering. Increases picking efficiency.



Self Lubrication & Cleaning System
Provides smooth operation. Increases chain & sprocket life.



Electrical Bale Ejection Easily ejects the bale with an electrical switch

SALIENT FEATURES



Safety Cover for Rollers Provides safe working environment.



Safety Cover at Scale Chamber To prevent exposure to rotating components.

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in







